



# Dlyte PRO500

## PRECISE METAL SURFACE FINISHING FOR MASS PRODUCTION

DlytePRO500 is the most advanced, powerful and versatile metal surface finishing equipment on the market specially designed for mass production. Its one-step automatic process reduces the complexity of current multi-step finishing processes, while improving cost efficiency and repeatability. This machine does not require a closed-up system to recycle water and sludge waste treatment machinery, therefore decreasing space, labor, and environmental licenses for waste management.

### FINISHING PROCESSES

- + Precision finishing
- + Smoothing
- + Mirror finishing
- + Deburring
- + Rounding
- + Corrosion resistance
- + AM post-processing

*Workbowl and cathode set are not included.*

## 01. MACHINE SPECIFICATIONS

TECHNICAL DATA	DIMENSION	Machine dimensions	1,300 x 2,770 x 1,380 mm
	CAPACITY	Electrolyte capacity	250 l
		Holder + piece area	Ø500 x 540 mm (x1) Ø200 x 540 mm (x8)
		Work piece area	Up to Ø500 x 250 mm (x1) Up to Ø200 x 200 mm (x8)
		Weight	50 kg (work piece(s) + holder) (x1) 20 kg (work piece(s) + holder) (x8)
MACHINE WEIGHT		Dlyte PRO500 weight	1600 kg
		Tank with electrolyte	400 kg
ELECTRICAL <sup>(1)</sup>		Rated power	25 KW <sup>(2)</sup>
		Short-circuit breaking capacity (ics)	6 kA
		Rated voltage	400 Vac ± 10% (3P+N+GND)
		Frequency	50 - 60 Hz
		Rated current	35 A
		Full load current	40 A
		Grounding connection	TN system
		Earth leakage current	> 10 mA <sup>(3)</sup>
AIR		Air supply (Main line)	6 - 7 bar (air connector Ø10 mm)
		Air flow (Main line)	1,000 l/min <sup>(4)</sup>
		Air supply (Holder line)	6 - 7 bar (air connector Ø12 mm)
		Air flow (Holder line)	1,500 l/min <sup>(4)</sup>
		Air quality (ISO 8573-1:2010)	- . 4 . - (dewpoint ≤ +3°C)
DISTILLED WATER		Water supply	Connection (Ø10 mm)
		Water tank	16 l
TEMPERATURE		Operating	5°C to 35 °C
		Dlyte PRO500 storage	-10°C to + 70°C
		Electrolyte storage	5°C to 40°C (max. 24 months)
PROTECTION INDEX		Machine	IP20
		Electric cabinets and peripherals	IP22
NOISE		Holder vibrators OFF (EN ISO 11202)	<70 dB
		Holder vibrators ON (EN ISO 11202)	74 dB (1 m); <70 dB (7m)

<sup>(1)</sup> The machine shall be connected to a power line with: A) Differential switch: 4P - 40A, 300mA – Type B. B) Circuit breaker switch: 4P - 40A, C curve. C) The female connector shall meet the IEC 60309 series. <sup>(2)</sup> Detailed power consumption in Table 2

<sup>(3)</sup> Note Leakage current: 20 mA. <sup>(4)</sup> Detailed air consumption in the last table.

## 02. DETAILED POWER CONSUMPTION

LOAD	CURRENT CONSUMPTION (A) 1 HOLDER	CURRENT CONSUMPTION (A) 8 HOLDERS	VOLTAGE (V)	POWER (W)	OTHER MODULES CONSUMPTION (W)	MACHINE POWER CONSUMPTION (W)
Low	10	80	30	2400	7000	9400
Medium	25	200	30	6000	7000	13000
High	45	360	30	10800	7000	17800
Max	45	360	50	18000	7000	25000

The power consumption depends on the total surface to be polished in one cycle.

## 03. DETAILED AIR CONSUMPTION

The air consumption required for each line is (the duty cycle is specified in percentage):

The air consumption required for each line is (the duty cycle is specified in percentage):			AIR CONSUMPTION (L/MIN)							
			INSERT THE CORE INTO THE TANK (8s)	POLISHING PROCESS				REMOVE THE CORE INTO THE TANK (8s)	CLEANING PROCESS	
LINE	FUNCTION	SPECIFICATION	Standard	Min	Most common	Max		Min	Med.	Max
Main Line	Up/Down movement	600	500 (100%)	0	0	500 (50%)	500 (100%)	-	-	-
	Holder gripping	600	-	-	-		-	-	-	-
	Electrolyte blowers	600	-	0	100 (20%)	100 (20%)	-	-	-	-
	Cleaning system	1000						600	1000	
Main Line	Holder vibration	500	-	-		500 (100%)		-	-	-
	Holder blowers	1000	-	-		1000 (100%)		-	-	-
TOTAL			500	0	100	2100	500	0	600	1000

Air shall never be required for both the polishing process and the cleaning process at the same time.

## 04. TECHNICAL DRAW

