

DLyte Desktop PRO

DLyte Desktop PRO[®] is an ultra-compact system that gathers all the advantages of any DLyte system currently available on the market. From grinding to mirror finishing, this set-up offers an easy way to process any casting, sintering or milling metal parts. It provides high-quality polishing for Cobalt-Chrome, Titanium, and Stainless Steel parts. It can be used in a wide range of materials, thanks to its complete range of parameters, including a combination of a high/low frequency process. It has the capacity to polish two pieces per working cycle within a maximum working volume of 80 x Ø 60 mm.

Cathode set, holder finger, holder mixer, and holder checking tool included.



FINISHING PROCESSES

- + Precision finishing
- + Smoothing
- + Mirror finishing
- + Deburring
- + Rounding
- + Corrosion resistance
- + AM post-processing

01. MACHINE SPECIFICATIONS

TECHNICAL DATA

| Capacity (per cycle) | 2 pieces |
|------------------------------------|-------------------------------------|
| Maximum piece dimensions | 80 x Ø 60 mm |
| Piece weight | 0.5 kg |
| Machine dimensions | 450 x 519 x 470 mm |
| Machine weight | 43 kg |
| Power | 1.7 kW |
| Full load current consumption | 8 A |
| Voltage | $230 V \sim \pm 10\% (1P + N + PE)$ |
| Frequency | 50-60 Hz |
| Short-circuit break capacity (LCS) | 0.3 kA |
| Grounding connection | TN system |
| Protection Index | IP 20 (polishing module) |
| | IP 22 (electrical cabinet) |
| Sound pressure level | <70 dB (A) |
| | |

*Optional transformer kit 110 V - 230 VAC

02. TECHNICAL DRAW







