

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 08.05.2020 Page 1 of 11

Rigid 10K Resin

SECTION 1: Identification

Product identifier

Product name: Rigid 10K Resin Product code: FLRG1001

Recommended use of the product and restriction on use

Relevant identified uses: For use in Formlabs SLA Printers **Uses advised against:** Not determined or not applicable.

Reasons why uses advised against: Not determined or not applicable.

Manufacturer or supplier details

Manufacturer:

United States

Formlabs, Inc 35 Medford St Suite 201 Somerville, MA 02143 +1 617 855 0762 sds@formlabs.com

Emergency telephone number:

United States/Canada

CHEMTREC 1-800-424-9300 (24/7)

SECTION 2: Hazard identification

GHS classification:

Skin sensitization, category 1 Chronic aquatic hazard, category 2

Label elements

Hazard pictograms:





Signal word: Warning

Hazard statements:

H317 May cause an allergic skin reaction

H411 Toxic to aquatic life with long lasting effects

Precautionary statements:

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P272 Contaminated work clothing should not be allowed out of the workplace

P280 Wear protective gloves/protective clothing/eye protection/face protection

P302+P352 IF ON SKIN: Wash with plenty of soap and water

P333+P313 If skin irritation or rash occurs: Get medical advice/attention

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 08.05.2020 Page 2 of 11

Rigid 10K Resin

P363 Wash contaminated clothing before reuse

P501 Dispose of contents/container in accordance with local/regional/national regulations

Hazards not otherwise classified:

None

SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: Trade Secret	Urethane Dimethacrylate	15-25
CAS number: Trade Secret	Methacrylate Monomer(s)	7-10
CAS number: Trade Secret	Photoinitiator(s)	<0.5
CAS number: Trade Secret	Filler	55-75

Additional Information: None

SECTION 4: First-aid measures

Description of first-aid measures

General notes:

Show this Safety Data Sheet to the doctor in attendance.

After inhalation:

If inhaled, remove person to fresh air and place in a position comfortable for breathing. Keep person at rest. If breathing is difficult, administer oxygen. If breathing has stopped, provide artificial respiration. If experiencing respiratory symptoms, seek medical advice/attention.

After skin contact:

Remove contaminated clothing and shoes. Rinse skin with copious amounts of water [shower] for several minutes. Launder contaminated clothing before reuse. If symptoms develop or persist, seek medical advice/attention.

After eve contact:

Rinse eyes with plenty of water for several minutes. Remove contact lenses if present and easy to do so. Protect unexposed eye. If symptoms develop or persist, seek medical advice/attention.

After ingestion:

If swallowed, DO NOT induce vomiting unless told to do so by a physician or poison control center. Rinse mouth with water. Never give anything by mouth to an unconscious person. If spontaneous vomiting occurs, place on the left side with head down to prevent aspiration of liquid into the lungs. If symptoms develop or persist, seek medical advice/attention.

Most important symptoms and effects, both acute and delayed

Acute symptoms and effects:

Dermal exposure may cause an allergic skin reaction. Symptoms may include irritation, redness, pain, rash, inflammation, itching, burning and dermatitis.

Delayed symptoms and effects:

Effects are dependent on exposure (dose, concentration, contact time).

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 08.05.2020 Page 3 of 11

Rigid 10K Resin

Immediate medical attention and special treatment

Specific treatment:

Not determined or not available.

Notes for the doctor:

Treat symptomatically.

SECTION 5: Fire-fighting measures

Extinguishing media

Suitable extinguishing media:

Water mist/fog, carbon dioxide, dry chemical, or alcohol resistant foam.

Unsuitable extinguishing media:

Do not use water jet.

Specific hazards during fire-fighting:

Thermal decomposition may produce irritating/toxic fumes/gases.

Special protective equipment for firefighters:

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full-face piece operated in positive pressure mode.

Special precautions:

Avoid contact with skin, eyes, hair and clothing. Do not breathe fumes/gas/mists/aerosols/vapors/dusts. Move containers from fire area if safe to do so. Use water spray/fog for cooling fire exposed containers. Avoid unnecessary run-off of extinguishing media which may cause pollution.

SECTION 6: Accidental release measures

Personal precautions, protective equipment, and emergency procedures:

Evacuate unnecessary personnel. Ventilate area. Extinguish any sources of ignition. Wear recommended personal protective equipment (see Section 8). Avoid contact with skin, eyes and clothing. Avoid breathing mist, vapor, dust, fume, and spray. Do not walk through spilled material. Wash thoroughly after handling.

Environmental precautions:

Prevent further leakage or spillage if safe to do so. Prevent from reaching drains, sewers and waterways. Discharge into the environment must be avoided.

Methods and material for containment and cleaning up:

Do not touch damaged containers or spilled material unless wearing appropriate personal protective clothing. Stop leak if you can do it without risk. Contain and collect spillage and place in suitable container for future disposal. Dispose of in accordance with all applicable regulations (see Section 13).

Reference to other sections:

For personal protective equipment see Section 8. For disposal see Section 13.

SECTION 7: Handling and storage

Precautions for safe handling:

Use appropriate personal protective equipment (see Section 8). Use only with adequate ventilation. Avoid breathing mist/vapor/spray/dust. Do not eat, drink, smoke, or use personal products when handling chemical substances. Avoid contact with skin, eyes, and clothing. Wash affected areas thoroughly after handling. Keep away from incompatible materials (See Section 10). Keep containers tightly closed when not in use.

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 08.05.2020 Page 4 of 11

Rigid 10K Resin

Conditions for safe storage, including any incompatibilities:

Store in cool, dry, well-ventilated location out of direct sunlight. Keep away from food and beverages. Protect from freezing and physical damage. Store away from heat, open flames and other sources of ignition. Keep container tightly sealed. Store away from incompatible materials (See Section 10).

SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

Occupational Exposure limit values:

No occupational exposure limits noted for the ingredient(s).

Biological limit values:

No biological exposure limits noted for the ingredient(s).

Information on monitoring procedures:

Not determined or not applicable.

Appropriate engineering controls:

Emergency eye wash stations and safety showers should be available in the immediate vicinity of use or handling. Provide adequate ventilation to maintain the airborne concentrations of vapor, mists, and/or dusts below the applicable workplace exposure limits, while observing recognized national standards (or equivalent).

Personal protection equipment

Eye and face protection:

Safety glasses or goggles. Use eye protection equipment that has been tested and approved by recognized national standards (or equivalent).

Skin and body protection:

Chemical resistant, impervious gloves approved by the appropriate standards. Gloves must be inspected prior to use. Avoid skin contact with used gloves. Appropriate techniques should be used to remove used gloves and contaminated clothing. Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Ensure that all personal protective equipment is approved by recognized national standards (or equivalent).

Respiratory protection:

If engineering controls do not maintain airborne concentrations below the applicable workplace exposure limits, or to an acceptable level (if exposure limits have not been established), a respirator approved by recognized national standards (or equivalent) must be worn.

General hygienic measures:

When handling chemical products, do not eat, drink, or smoke. Wash hands after handling, before breaks, and at the end of the workday. Avoid contact with skin, eyes, and clothing. Wash contaminated clothing

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 08.05.2020 Page 5 of 11

Rigid 10K Resin

before reuse. Perform routine housekeeping.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

White Liquid
Characteristic acrylate
Not determined or not available.
Not determined or not available.
Not determined or not available.
>100°C
>93.5°C
Not determined or not available.
Not Flammable
Not determined or not available.
1.63 g/cm3
Not determined or not available.
1896 cps @ 25°C; 933 cps @ 35°C
Not determined or not available.
Not determined or not available.
Not determined or not available.

Other information

SECTION 10: Stability and reactivity

Reactivity:

Not reactive under recommended handling and storage conditions.

Chemical stability:

Stable under recommended handling and storage conditions.

Possibility of hazardous reactions:

Hazardous reactions are not anticipated under recommended conditions of handling and storage.

Conditions to avoid:

Extreme heat, open flames, hot surfaces, sparks, ignition sources and incompatible materials. Avoid storage >38°C (100°F) and exposure to light/direct sunlight and heat.

Incompatible materials:

Polymerization initiators, including peroxides, strong oxidizing agents, alcohols, copper, copper alloys, carbon steel, iron, rust, and strong bases.

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 08.05.2020 Page 6 of 11

Rigid 10K Resin

Hazardous decomposition products:

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

Acute toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Route	Result
Methacrylate Monomer(s)	oral	LD50 Rat: >2000 mg/kg
	dermal	LD50 Rabbit: >3000 mg/kg
Photoinitiator(s)	oral	LD50 Rat: >5000 mg/kg

Skin corrosion/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available. Substance data:

Name	Result
Methacrylate Monomer(s)	Causes skin irritation

Serious eye damage/irritation

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available. Substance data:

Name	Result
Methacrylate Monomer(s)	Causes serious eye irritation

Respiratory or skin sensitization

Assessment:

May cause an allergic skin reaction.

Product data: No data available. Substance data:

Name	Result
Urethane Dimethacrylate	May cause an allergic skin reaction.
Photoinitiator(s)	May cause an allergic skin reaction.

Carcinogenicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available. Substance data: No data available.

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 08.05.2020 Page 7 of 11

Rigid 10K Resin

International Agency for Research on Cancer (IARC): None of the ingredients are listed.

National Toxicology Program (NTP): None of the ingredients are listed.

Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:No data available.

Substance data: No data available.

Reproductive toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data:No data available.

Substance data: No data available.

Specific target organ toxicity (single exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available. Substance data:

Name	Result
Methacrylate Monomer(s)	May cause respiratory irritation

Specific target organ toxicity (repeated exposure)

Assessment: Based on available data, the classification criteria are not met.

Product data:No data available.

Substance data: No data available.

Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

SECTION 12: Ecological information

Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 08.05.2020 Page 8 of 11

Rigid 10K Resin

Product data: No data available.

Substance data:

Name	Result
Methacrylate Monomer(s)	LC50 Danio rerio: 1.79 mg/L (96 hours)
	EC50 Daphnia magna: 2.57 mg/L (48 hours)

Chronic (long-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

Substance data:

Name	Result
Methacrylate Monomer(s)	NOEC Daphnia magna: 0.233 mg/L (21 days)

Persistence and degradability

Product data: No data available.

Substance data:

Name	Result
Urethane Dimethacrylate	This substance is not readily biodegradable.
Methacrylate Monomer(s)	Readily biodegradable
Photoinitiator(s)	The substance is not readily biodegradable.

Bioaccumulative potential

Product data: No data available.

Substance data:

Name	Result
Photoinitiator(s)	This substance is not expected to bioaccumulate because of log Kow (2.91).

Mobility in soil

Product data: No data available.

Substance data:

Name	Result
•	This substance is expected to distribute between the water column and organic soil and sediment particles.
Photoinitiator(s)	This substance is expected to be adsorbed by the soil.

Results of PBT and vPvB assessment

Product data:

PBT assessment: This product does not contain any substances that are assessed to be a PBT. vPvB assessment: This product does not contain any substances that are assessed to be a vPvB.

Substance data:

PBT assessment:

Urethane Dimethacrylate	This substance is not PBT.
Methacrylate Monomer(s)	This substance in not PBT
Photoinitiator(s)	This substance is not PBT.

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 08.05.2020 Page 9 of 11

Rigid 10K Resin

vPvB assessment:

Urethane Dimethacrylate	This substance is not vPvB.
Methacrylate Monomer(s)	This substance is not vPvB
Photoinitiator(s)	This substance is not vPvB.

Other adverse effects: No data available.

SECTION 13: Disposal considerations

Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities. Do not discharge into public wastewater or surface waters.

Contaminated packages:

Dispose in a safe manner in accordance with local and national regulations. Do not allow the product to be released into the environment.

SECTION 14: Transport information

Canadian Transportation of Dangerous Goods (TDG)

UN number	UN 3082	
UN proper shipping name	Environmentally hazardous liquid, N.O.S. Methacrylate Polymer	
UN transport hazard class(es)	9	
Packing group	III	
Environmental hazards	Marine Pollutant	
Special precautions for user	for user None	
Additional Information	This product is not regulated as a dangerous good when transported in sizes of $\leq 5L$ or ≤ 5 kg provided the packaging meets the general provisions of TDG schedule 1 provision 99.	

International Maritime Dangerous Goods (IMDG)

UN number	UN 3082		
UN proper shipping name	Environmentally hazardous liquid, N.O.S. Methacrylate Polymer		
UN transport hazard class(es)	9		
Packing group	III		
Environmental hazards	Marine Pollutant		
Special precautions for user	None		
Additional Information	This product is not regulated as a dangerous good when transported in sizes of $\leq 5L$ or ≤ 5 kg provided the packaging meets the general provisions of 4.1.1.1, 4.1.1.2 and 4.1.1.4 to 4.1.1.8.		

International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

According to Canadian Hazardous Products Regulations and WHMIS 2015

Initial preparation date: 08.05.2020 Page 10 of 11

Rigid 10K Resin

UN number	UN 3082	
UN proper shipping name	Environmentally hazardous liquid, N.O.S. Methacrylate Polymer	
JN transport hazard class(es) 9		
Packing group	III	
Environmental hazards	Marine Pollutant	
Special precautions for user	None	
Additional Information	This product is not regulated as a dangerous good when transported in sizes of $\leq 5L$ or $5\leq kg$ provided the packaging meets the general provisions of 5.0.2.4.1, 5.0.2.6.1 and 5.0.2.8.	

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code		
Bulk Name	None	
Ship type	None	
Pollution category	None	

SECTION 15: Regulatory information

Canada regulations

Domestic substances list (DSL):

Trade Secret	Urethane Dimethacrylate	Not Listed
Trade Secret	Methacrylate Monomer(s)	Listed
Trade Secret	Photoinitiator(s)	Listed

Non-domestic substances list (NDSL):

Trade Secret	Urethane Dimethacrylate	Listed
Trade Secret	[Not Listed
Trade Secret	Photoinitiator(s)	Not Listed

SECTION 16: Other information

Abbreviations and Acronyms: None

Disclaimer:

This product has been classified in accordance with the Canadian Hazardous Products Regulations and WHMIS 2015. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation, and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

Initial preparation date: 08.05.2020

End of Safety Data Sheet